WE MAKE NETWORKING EASY!

## Niveo Professional Enterprise Series

# NGSME8H family

8-port Gigabit PoE+ managed switches with two Gigabit SFP ports.





**PRODUCT DATASHEET**

# Product Specification

## Introduction

NGSME8H(s)(x),(-AV) is 8-(rear)port 10/100/1000Base-T + 2 Gigabit SFP L2+ Management PoE Switch that is designed for small or medium network environment to strengthen its network connection. The 8 10/100/1000Base-T ports support IEEE 802.3at PoE technology, up to 30W per port and maximum 100m transmission distance. The switch equipped with AC to DC power module to support 130W and 235 W ( NGSME8Hx power budget for PoE power. The added 2 SFP slots support 100M and Gigabit Fiber transceiver for long distance transmission. The switch also supports Layer 2+ full management software features. These features are powerful to provide PoE Control, Network Control, Management, Monitor and Security features' requests. It is a superb choice to boost your network with better performance, efficiency and high PoE power consumption.

## IEEE 802.3at Power over Ethernet (PoE) ports

The switch features 8 IEEE 802.3at Power over Ethernet (PoE) ports supplying up to 30 watts per port. This product can convert standard 100~240V/AC power into low-voltage DC that runs over existing LAN cable to power up IEEE 802.3at compliant network accessories. It also features PoE awareness to verify whether the network device receive power is IEEE 802.3at compliant, or only the data will be sent through LAN cable. By adding the switch to the existing networking, installing networking products such as Access Points and IP cameras can be easily managed and set up. Wireless device deployments are easily located with available power outlets and network administrators don't need to use heavy AC power adapters anymore.

## 2 Gigabit SFP Open Slots

The switch supports 2 additional SFP open slots to uplink to servers, storage, or other switching devices for long loop reach applications. The 2 SFP slots can support different types, speed and distance SFP transceivers. It also supports legacy 100M SFP transceiver. If the 100M fiber infrastructure is constructed and 100M bandwidth is enough, the 100M SFP transceiver can be an optional choice for the legacy 100M network environment.

## Full Layer 2+ Management Features

The switch includes full Layer 2+ Management features. The software set includes up to 4K 802.1Q VLAN and advanced Protocol VLAN, Private VLAN, MVR…advanced VLAN features. There are 8 physical queues Quality of Service, IPv4/v6 Multicast filtering, Rapid Spanning Tree protocol to avoid network loop, Multiple Spanning Tree Protocol to integrate VLAN and Spanning Tree, LACP, LLDP; sFlow, port mirroring, cable diagnostic and advanced Network Security features. It also provides Console CLI for out of band management and SNMP, Web GUI for in band Management.

## Advanced Security

The switch supports advanced security features. For switch management, there are secured HTTPS and SSH, the login password, configuration packets are secured. The port binding allows to bind specific MAC address to the port, only the MAC has the privilege to access the network. The 802.1X port based Access Control, every user should be authorized first when they want to access the network. AAA is the short of the Authentication, Authorization and Accounting with RADIUS, TACAS+ server. Layer 2+ Access Control List allows user to define the access privilege based on IP, MAC, Port number…etc.

NGSME8H family

# Specifications

| | | |
|---|---|---|
| **Interface** | | |
| 10 Base-T/100 Base-TX/1000 Base-T RJ45 Ports | | 8 |
| 100/1000Base-SX/LX SFP Port | | 2 |
| Console Port for CLI Management | | 1 |
| **System Performance** | | |
| Packet Buffer | | 4Mbits |
| MAC Address Table Size | | 8K |
| Switching Capacity | | 20Gbps |
| Forwarding Rate | | 14.88Mpps |
| **PoE Features** | | |
| IEEE 802.3 af/at | | IEEE 802.3 af/at |
| Number of PSE Ports | | 8 |
| Max. PoE Budget | | 130W /235W X version |
| External/Internal Power | | Internal Power |
| Power Feeding Detecting Capability on PD | | • |
| PD Alive Check | | • |
| PD Classification | | • |
| Power Management (per-port) | Enable/Disable PoE Per Port | • |
| | Priority Setting Per Port | • |
| | Power Level Setting Per Port | • |
| | Overloading Protection | • |
| **L2 Features** | | |
| Auto-negotiation | | • |
| Auto MDI/MDIX | | • |
| Flow Control (duplex) | 802.3x (Full) | • |
| | Back-Pressure (Half) | • |
| Spanning Tree | IEEE 802.1D (STP) | • |
| | IEEE 802.1w (RSTP) | • |
| | IEEE 802.1s (MSTP) | • |
| VLAN | VLAN Group | 4K |
| | Tagged Based | • |
| | Port-based | • |
| | Voice VLAN | Voice VLAN with OUI |
| Link Aggregation | IEEE 802.3ad with LACP | • |
| | Static Trunk | • |
| | Max. LACP Link Aggregation Group | 5 |
| | Max. Port per Link Aggregation Group | 8 |
| IGMP Snooping | IGMP Snooping v1/v2/v3 | Supports 1024 IGMP groups |
| | IGMP Static Multicast Addresses | Supports 1024 static multicast addresses |
| | IPv6 MLD Snooping | Supports 1024 MLD groups |
| | MLD Static Multicast Addresses | Supports 1024 static multicast addresses |
| | Querier, Immediate Leave | • |
| Storm Control (Broadcast/Multi-cast/Un-known Unicast) | | • |
| Jumbo Frame Support | | 9.6KB |
| **QoS Features** | | |
| Number of priority queue | | 8 queues/port |
| Rate Limiting | Ingress | Yes, 1KBps/1pps |
| | Egress | Yes, 1KBps/1pps |
| DiffServ (RFC2474 Remarking) | | • |
| Scheduling (WRR, Strict, Hybrid) | | • |
| CoS | IEEE 802.1p | • |
| | IP ToS precedence, IP DSCP | • |
| **Security** | | |
| Management System User Name/Password Protection | | • |
| User Privilege | | Set user privilege up to 15 Level |
| Port Security (MAC-based) | | • |
| IEEE 802.1x Port-based Access Control | | • |
| ACL (L2/L3/L4) | | • |
| IP Source Guard | | • |
| RADIUS (Authentication, Authorization, Accounting) | | • |
| TACACS+ | | • |
| HTTP & SSL (Secure Web) | | • |
| SSH v2.0 (Secured Telnet Session) | | • |
| MAC/IP Filter | | • |

## NGSME8H family

| | |
|---|---|
| **Management** | |
| Command Line Interface (CLI) | • |
| Web Based Management | • |
| Telnet | • |
| Access Management Filtering | SNMP/WEB/SSH/TELNET |
| Firmware Upgrade via HTTP | • |
| Dual Firmware Images | • |
| Configuration Download/Upload | • |
| SNMP (v1/v2c/v3) | • |
| RMON (1,2,3,&9 groups) | • |
| DHCP (Client/Relay/Option82/Snooping) | • |
| System Event/Error Log | • |
| NTP/LLDP | • |
| Cable Diagnostics | • |
| IPv6 Configuration | • |
| Port Mirroring | Many to One |
| **Mechanical** | |
| Power Input | 100~240VAC |
| Dimension (H*W*D) | 44*330*210 mm |
| LED | Power, PoE, Link/Act, SFP |
| Operating Temperature | 0~45°C |
| Storage Temperature | -20~80°C |
| Operating Humidity | 5~90% (non-condensing) |
| Weight | 2.2 KG |
| Certification | CE, FCC cULus |
| **Standard** | |
| IEEE 802.3 – 10Base-T | • |
| IEEE 802.3u - 100Base-TX | • |
| IEEE 802.3ab - 1000Base-T | • |
| IEEE 802.3z - 1000 Base-SX/LX | • |
| IEEE 802.3af - Power over Ethernet (PoE) | • |
| IEEE 802.3at - Power over Ethernet (PoE+) | • |
| IEEE 802.3az - Energy Efficient Ethernet (EEE) | • |
| IEEE 802.3x - Flow Control | • |
| IEEE 802.1Q - VLAN | • |
| IEEE802.1v - Protocol VLAN | • |
| IEEE 802.1p - Class of Service | • |
| IEEE 802.1D - Spanning Tree | • |
| IEEE 802.1w - Rapid Spanning Tree | • |
| IEEE 802.1s - Multiple Spanning Tree | • |
| IEEE 802.3ad - Link Aggregation Control Protocol (LACP) | • |
| IEEE 802.1AB - LLDP (Link Layer Discovery Protocol) | • |
| IEEE 802.1X - Access Control | • |